

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A color matching server for converting color data based on color matching information that permits reproduction of prescribed standard colors, wherein said color matching server can communicate with a client, and wherein said color matching server ~~comprises~~ is operable to:

~~a means to~~ acquire from said client data relating to actual colors printed by a printer associated with said client[[,]] ;

~~a means to~~ create said color matching information based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors[[,]] ; and

~~a means to~~ send the color matching information to said client, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors.

2. (Currently Amended) A color matching client for converting color data to prescribed standard colors, wherein said client is operable to ~~comprising~~:

~~a means to~~ send to a server data of actual colors printed by a printer associated with said client in the environment of said client[[,]] ;

~~a means to~~ acquire color matching information for said actual colors from said server, wherein said color matching information permits reproduction of prescribed standard colors and is determined based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors[[,]] ; and

~~a means to~~ convert color data based on said color matching information to said prescribed standard colors.

3. (Currently Amended) A print control server ~~which is connected for two-way communications to a print control client to perform conversion~~ for performing color conversion based on prescribed color matching information that permits reproduction of prescribed standard colors at the time of conversion into color data corresponding to a plurality of printing colorants upon input of print data ~~and which creates said color matching information based on data measured by said print control client and sends it to said print control client~~, said print control server comprising:

a measured data acquiring ~~means to~~ component capable of acquiring ~~acquire~~ the measured data of the image for colorimetry having a plurality of tones for each of said printing colorants which is printed by said print control client[[,]] ;

a color matching information creating component capable of creating ~~means to create~~ said color matching information based on the measured data of the image for colorimetry for said individual printing colorants and the measured data of said standard colors corresponding to the printing colorants which have previously been acquired[[,]] ; and

a color matching information output component capable of outputting ~~means to output~~ the color matching information ~~created by the color matching creating means to said print control client~~.

4. (Currently Amended) A print control client ~~which is connected for two-way communications to~~ capable of communicating with a print control server to perform conversion of color data based on color matching information that permits reproduction of prescribed standard colors at the time of conversion into color data corresponding to a plurality of printing colorants upon input of print data, said client comprising:

a colorimetry image print controller capable of controlling ~~means to control~~ the printing of images for colorimetry with a plurality of tones for each of said printing colorants to determine measured data[[,]] ;

~~a data sending means to receive~~ receiver/sender capable of receiving ~~as input~~ the measured data of the images and ~~sends~~ sending it to said print control server[[,]] ;

~~a matching color information acquisition means to acquire~~ an acquiring component capable of acquiring said color matching information from said print control server[[,]] ; and

~~a means to convert~~ convertor capable of converting said print data into said color data based on said color matching information.

5. (Original) A print control server as defined in Claim 3, wherein the measured data of said print control client is lightness data of the image for colorimetry with a plurality of tones for each of said printing colorants.

6. (Currently Amended) A print control client as defined in Claim 4, wherein the measured data of said image for colorimetry is lightness data and said ~~data sending~~ means receiver/sender receives the input of the lightness data of the image for colorimetry and sends it to said print control server.

7. (Currently Amended) A print control system ~~which is composed of~~ that includes: (a) a print control client ~~to perform conversion for color conversion~~ based on prescribed color matching information that permits reproduction of prescribed standard colors at the time of printing using color data at the time of conversion into color data corresponding to a plurality of printing colorants upon input of print data, and (b) a print control server which is connected for two-way communications to the print control client and which creates said color matching information and sends it to said print control client,

wherein said print control client ~~comprising~~ comprises:

a colorimetry image print controllor ~~control means to perform control to print~~ capable of controlling the printing of colorimetry images with a plurality of tones for each of said printing colorants[[,]] ;

a lightness data receiver/sender ~~sending means to receive~~ capable of receiving the input of the lightness data of said colorimetry image and sending it to said print control server[[,]] ; and

a color matching information acquisition ~~means to acquire~~ component capable of acquiring said color matching information from said print control server[[,]] ;

wherein said print control server ~~comprising~~ comprises:

a standard color lightness data storing region in which is stored the lightness data of said standard color[[,]] ;

a lightness data acquisition ~~means to acquire~~ component capable of acquiring the lightness data of the colorimetry image for each of said printing colorants which is printed by said print control client[[,]] ;

a color matching information creating ~~means to create~~ component capable of creating said color matching information based on the lightness data of the

colorimetry image for each of said printing colorants and the lightness data of said standard colors corresponding to the printing colorants[[],] ; and

a color matching information output ~~means to output to~~ component capable of outputting to said print control client the color matching information created by the color matching information creating means,
said print control client:

~~prints said colorimetry image for each of the printing colorants by said colorimetry image print control means, receives the input of the lightness data of said colorimetry image by said lightness data sending means, and sends it to said print control means, and~~
said print control server:

~~receives the lightness data from said print control client by said lightness data acquisition means, creates the color matching information by said color matching information creating means based on the lightness data and said lightness data stored in said standard color lightness data storing region, and sends the thus created color matching information to said print control means by said color matching information output means,~~

said print control client:

~~acquires said color matching information from said print control server by said color matching information acquisition means, and converts said print data into said color data based on the color matching information.~~

8. (Currently Amended) A print control system as defined in Claim 7, wherein said print control client ~~has~~ further includes an image data sending ~~means to acquire~~ component capable of acquiring image data from an image capturing equipment to capture image data of an image for colorimetry and sending it to said print control server, and said lightness data acquisition ~~means~~ component converts the image data entered from said print control client into the lightness data, thereby acquiring the lightness data of said image for colorimetry.

9. (Original) A print control system as defined in Claim 8, wherein said image capturing equipment is a scanner.

10. (Original) A print control system as defined in Claim 7, wherein said color matching information is a tone value correction table which makes the tone value of the color data converted from said print data correspond to the tone value for color reproduction to match said standard color with printing colorants corresponding to said color data.

11. (Original) A print control system as defined in Claim 7, wherein said color matching information is provided in the form of color conversion table in which the relation between input and output is corrected.

12. (Currently Amended) A print control system as defined in Claim 7, wherein said print control client ~~is constructed of~~ includes a first and second print control clients, said first print control client comprising a standard color lightness data sending ~~means to receive~~ component capable of receiving the input of the lightness data of said standard colors and ~~sends~~ sending to said print control server the lightness data of standard colors which has been entered[[,]] ;

said print control server comprising a standard color lightness data storing ~~means~~ to store component capable of storing in said standard color lightness data storing region the lightness data of said standard colors which is entered from said first print control client[[,]] ; and

wherein said color matching information output ~~means~~ component outputs to said second print control client said color matching information which has been created based on the lightness data of said standard colors entered from said first print control client.

13. (Currently Amended) A print control system as defined in Claim 12, wherein the standard color lightness data storing ~~means~~ component of said print control server is capable of storing said lightness data entered from a plurality of said first print control clients for the first print control clients individually, said print control server has a list outputting ~~means to create~~ component capable of creating a list of the first print control clients which entered the lightness data and ~~outputs~~ outputting it to said second print control client; ~~clients~~,

said second print control client ~~clients~~ has a select input receiving ~~means to~~ component capable of selecting a ~~make one select~~ specific first print control client ~~clients~~ based on the list output from by said list output ~~means~~ component, and a select

result output ~~means to send~~ component capable of sending data to the selected specific first print control client; ~~selected and input to said print control server,~~

said color matching information creating ~~means~~ component capable of specifying ~~specifies~~ the lightness data of said standard colors based on said selected specific first print control client ~~and input first print control client which has been sent from said select result output means,~~ thereby creating said color matching information corresponding to the lightness data of said second print control client[[,]] ; and

said color matching information output ~~means outputs~~ component capable of outputting said color matching information to said second print control clients.

14. (Currently Amended) A print control system as defined in Claim 7, wherein said print control client has an identification information sending ~~means which~~ component capable of acquiring ~~acquires~~ the identification information of the equipment which reproduces colors with said printing colorants and ~~sends~~ sending it to said print control server, and said color matching information creating ~~means~~ component is capable of creating ~~creates~~ said color matching information based on the lightness data of said standard colors corresponding to the identification information entered from said print control client.

15. (Currently Amended) A print control method to be carried out by a print control server which is connected for two-way communications to a print control client to perform conversion based on prescribed color matching information that permits reproduction of prescribed standard colors at the time of conversion into color data corresponding to a plurality of printing colorants upon input of print data and which creates said color matching information based on data measured by said print control client and sends it to said print control client, said method comprising:

~~a measured data acquisition step to acquire~~ acquiring measured data of colorimetry images with tones for individual printing colorants which are printed by said print control client[[,]] ;

~~a color matching information creating step to create~~ creating said color matching information based on the measured data of colorimetry image for each of said printing colorants and the measured data of said standard colors corresponding to said printing colorants which have previously been obtained[[,]] ; and

~~a color matching information output step to output~~ outputting the color matching information ~~created by the color matching information creating step to said print control client.~~

16. (Currently Amended) A computer readable medium storing therein a print control computer program code for a print control server ~~which is connected for two-way communications to a print control client to perform~~ for color conversion based on prescribed color matching information that permits reproduction of prescribed standard colors at the time of conversion into color data corresponding to a plurality of printing colorants upon input of print data ~~and which creates said color matching information based on data measured by said print control client and sends it to said print control client,~~ said computer readable medium comprising:

computer program code for ~~a measured data acquisition function to acquire~~ acquiring measured data of colorimetry images with tones for individual printing colorants which are printed by said print control client[[,]] ;

computer program code for ~~a color matching information creating function to create~~ creating said color matching information based on the measured data of colorimetry image for each of said printing colorants and the measured data of said standard colors corresponding to said printing colorants which have previously been obtained[[,]] ; and

computer program code for ~~a color matching information output function to output~~ outputting the color matching information ~~created by the color matching information creating step to said print control client.~~

17. (Currently Amended) A profile providing server which comprises:

a communicating ~~means~~ component capable of transmission and reception of data through a communication line[[,]] ;

a read color data acquisition ~~means to acquire~~ component capable of acquiring through said communication line the read color data obtained by reading with a prescribed image input device the color charts printed by a specific printing device based on prescribed print color data[[,]] ;

a color character description data acquisition ~~means to acquire~~ component capable of acquiring through a prescribed interface the color character description data

to match the print color data of the image input device with the prescribed standard color space coordinate values[[,]] ;

a profile data creating ~~means to create~~ component capable of creating the profile data defining correspondence between the printed color data and the prescribed standard color space coordinate values by matching the read color data with the standard color space coordinate value with reference to the color character description data[[,]] ; and

a profile data output ~~means to output~~ capable of outputting through the communication line the thus created profile data.

18. (Currently Amended) A profile demanding client to connect and control a printing device and an image input device and to demand a profile of the printing device for an external server, which comprises:

a color chart print demand receiving ~~means to receive~~ component capable of receiving a demand to print a prescribed color chart by said printing device[[,]] ;

a printing control ~~means to control~~ component capable of controlling the print execution by said printing device based on a prescribed printing color data in compliance with the printing demand from said color chart print demand receiving ~~means,~~ component;

a color chart reading demand receiving ~~means to receive~~ component capable of receiving a demand to read by said image input device the color chart printed in accordance with the control effectively provided by said print control component; ~~according to control from said print control means,~~

an image input device control ~~means to control~~ component capable of controlling said image input device in compliance with the read demand from said color chart reading demand receiving ~~means~~ component and ~~acquires~~ acquiring the read color data of said color chart[[,]] ;

a color character description data acquisition ~~means to control~~ component for controlling said image input device and ~~acquire~~ acquiring the color character description data previously stored in said image input device, said data matching the read color data with the prescribed standard color space coordinate value and being measured for the individual input image devices[[,]] ;

a communication ~~means~~ component capable of transmission and reception of data through a communication line[[,]] ;

a data output ~~means to output~~ component capable of outputting said printing color data, said read color data, and said color character description data through said communication ~~means~~, component; and

a profile data acquisition ~~means to acquire~~ component capable of acquiring the profile data of the printing device through said communication ~~means~~ component.

19-28. (Canceled)

29. (Currently Amended) A computer-implemented method for converting color data based on color matching information that permits reproduction of prescribed standard colors, said computer-implemented method comprising:

acquiring from a client data relating to actual colors printed by a printer associated with said client, wherein said data relating to actual colors is stored on a computer readable medium[[,]] ;

creating said color matching information based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors[[,]] ; and

sending the color matching information to said client, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors.

30. (Previously Presented) A computer-implemented method as recited in claim 29, wherein said method is performed by a server.

31. (Currently Amended) A computer readable medium including computer program code for converting color data based on color matching information that permits reproduction of prescribed standard colors, said computer readable medium comprising:

computer program code for acquiring from a client data relating to actual colors printed by a printer associated with said client[[,]] ;

computer program code for creating said color matching information based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors[[,]] ; and

computer program code for sending the color matching information to said client, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors.

32. (Currently Amended) A computer-implemented method for converting color data to prescribed standard colors, said computer-implemented method comprising:

 sending to a server data of actual colors printed by a printer associated with a client in the environment of said client[.,.] ;

 acquiring color matching information for said actual colors from said server, wherein said color matching information is stored on a computer readable medium, and wherein said color matching information permits reproduction of prescribed standard colors and is determined based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors[.,.] ; and

 converting color data based on said color matching information to said prescribed standard colors.

33. (Currently Amended) A computer readable medium including computer program code for converting color data to prescribed standard colors, said computer readable medium comprising:

 computer program code for sending to a server data of actual colors printed by a printer associated with a client in the environment of said client[.,.] ;

 computer program code for acquiring color matching information for said actual colors from said server, wherein said color matching information permits reproduction of prescribed standard colors and is determined based on said data relating to actual colors printed and data relating to said prescribed standard colors that effectively describes said prescribed standard colors, thereby allowing said client to use said color matching information to convert said color data to said prescribed standard colors[.,.] ; and

 computer program code for converting color data based on said color matching information to said prescribed standard colors.

34. (New) A print control system as defined in Claim 7,

wherein said print control client prints said colorimetry image for each of the printing colorants by using said colorimetry image print control component, receives the input of the lightness data of said colorimetry image by said lightness data sending component, and sends it to said print control component; and

wherein said print control server receives the lightness data from said print control client by said lightness data acquisition component, creates the color matching information by using said color matching information creating component based on the lightness data and said lightness data stored in said standard color lightness data storing region, and sends the created color matching information to said print control component by said color matching information output component.

35. (New) A print control system as defined in Claim 34, wherein said print control client further acquires said color matching information from said print control server by said color matching information acquisition means, and converts said print data into said color data based on the color matching information.